

# EXTERIOR

## TORQUE SPECIFICATIONS

### Front Bumper

| Part tightened                    | N*m | kgf*cm | ft.*lbf    |
|-----------------------------------|-----|--------|------------|
| Front bumper reinforcement x Body | 70  | 713    | 51         |
| Front bumper side retainer x Body | 6.0 | 61     | 53 in.*lbf |

SS

### Rear Bumper

| Part tightened                   | N*m | kgf*cm | ft.*lbf |
|----------------------------------|-----|--------|---------|
| Rear bumper reinforcement x Body | 37  | 377    | 27      |

### Rear Spoiler

| Part tightened      | N*m | kgf*cm | ft.*lbf    |
|---------------------|-----|--------|------------|
| Rear spoiler x Body | 7.5 | 76     | 66 in.*lbf |

### Roof Rack

| Part tightened                      | N*m          | kgf*cm   | ft.*lbf          |
|-------------------------------------|--------------|----------|------------------|
| Roof rack bar x Roof rack bar joint | 1.96 to 2.94 | 20 to 30 | 17 to 26 in.*lbf |
| Roof rack leg x Body                | 38           | 387      | 28               |
| Roof rack x Roof rack leg           | 2.8 to 5.0   | 29 to 51 | 25 to 43 in.*lbf |